

**UKCA**  
**DECLARATION OF CONFORMITY**  
**N. 6-UKCA**

1. Unique identification code of the product type:  
**DRY-PRESSED CERAMIC TILES, WITH WATER ABSORPTION E > 10%**
2. Intended use or uses:  
**FOR INTERNAL WALLS**
3. Name or registered trade mark, and contact address of the manufacturer:  
**KERABEN GRUPO S.A.U. Ctra. Valencia-Barcelona Km 44,3 12520 Nules (Castellón) España**
4. System o systems of assessment and verification of constancy of performance:  
**System 4**
5. Name and identification number of notified laboratory: **Not applicable**
6. Declared performances:

Essential characteristics		Performance	Harmonised technical specification
Reaction to fire (Decision 96/603/EEC amended)		Class A1	BS EN 14411
Breaking strength (ISO 10545-4)		≥ 600 N	
Adhesion with cement adhesive type		Class C1: ≥ 0,5 N/mm <sup>2</sup>	
Emissions of dangerous substances (Cadmium/lead emissions)		NPD	
Durability for	Internal use	Complies	


*The performance of the product identified in point 1 is in conformity with the declared performance in point 6.*

*This declaration of conformity is issued under the sole responsibility of the manufacturer identified in point 3.*

*NPD: No Performance Determined*

- Please check before fixing: model, shade, calibre and quality. Do not mix calibers.
- Product not suitable for exterior use.
- The material must be placed with the following minimum joint width: 1,5 mm for rectified products or 2,5 mm for non-rectified products.
- On walls with internal angles, 5 mm of space must be left free for possible expansion of the tiles. It will be necessary to correctly and accurately plan and do 5 mm perimeter boundary joints on surfaces greater then 7 sq meters, and 5 mm of expansion, every 20 to 40 sq meters of surface for exteriors and double that for interiors. Laying without joints is not recommended from a technical point of view.
- In the placement in places in contact with water (shower, kitchens, etc), it is recommended to use a waterproof-epoxy grout and guarantee the impermeabilitation of the coating.
- It is advisable to protect the floors and walls if, after placement, other work needs to be carried out involving the use or dragging of objects, such as ladders, as well as protecting them against scratches, stains or knocks in case any objects are dropped during this work.
- Do not bond.
- In the cleaning of tiles, not use powder detergents, neither acidic nor alkaline solutions, neither cleaning pads nor abrasive elements. It is enough to use a neutral liquid soap and a wet cloth.
- Laying the tiles means that they have been accepted, and, as a result, no claims will be accepted for material installed, arising from a failure to comply with these premises.

KERABEN GRUPO, S.A.U.



Ricardo Martínez Rodríguez  
Director of Quality Department